

The deliveries of coated bands follow the European and possibly Czech Technical Standards. The reference Standards for ordering of the coating and for the delivery of strips, straps and sheets are following:

ALUMINIUM AND ALUMINIUM ALLOYS

EN 1396,	Aluminium and aluminium alloys – Coil coated sheet and strip for general applications - Specifications
EN 485-1	Aluminium and aluminium alloys; sheet, strip and plate; Part 1: Technical delivery conditions
EN 485-2+A1	Aluminium and aluminium alloys; sheet, strip and plate; Part 2: Mechanical characters
EN 485-4	Aluminium and aluminium alloys; sheet, strip and plate; Part 4: Tolerances on shape and dimensions for cold-rolled products
EN 515	Aluminium and aluminium alloys; wrought products; temper designations
EN 573-3	Aluminium and aluminium alloys - Chemical composition and form of wrought products - Part 3: Chemical composition

COLD ROLLED STEEL

EN 10169	Continuously organic coated (coil coated) steel flat products - Technical delivery conditions
EN 10130	Cold rolled low carbon steel flat products for cold forming - Technical delivery conditions
EN 10140	Cold rolled narrow steel strip - Tolerances on dimensions and shape
EN 10025-1	Hot rolled products of structural steels – Part 1 General technical delivery conditions
EN 10111	Continuously hot rolled low carbon steel sheet and strip for cold forming - Technical delivery conditions

HOT-DIP COATED STEEL

EN 10169	Continuously organic coated (coil coated) steel flat products – Technical delivery conditions
EN 10346	Continuously hot-dip coated steel flat products - Technical delivery conditions
EN 10143	Continuously hot-dip metal coated steel sheet and strip - Tolerances on dimensions and shape
EN 10152	Electrolytically zink coated cold rolled steel flat products for cold forming – Technical delivery conditions
EN 10021	General technical delivery requirements for steel and iron products

In case of need the Buyer may agree with the Seller the delivery of raw or coated materials in accordance with other Standards acceptable for both Parties.

FACILITY OUTPUT	THICKNESS OF THE STRIP, STRAP, SHEET		WIDTH OF THE STRIP, STRAP, SHEET MM	RM MAX N/MM ²	LENGTH OF THE SHEET MM	INTERNAL DIAMETER OF THE STRIP, STRAP MM	EXTERNAL DIAMETER OF THE STRIP, STRAP		WEIGHT OF THE STRIP, STRAP, STACK	
	MM						MM		KG	
	Al	Steel					Al	Steel	Al	Steel
COIL COATING LINE	0,4-2,0	0,3-1,2	600-1340	400	-	406/508/610	2 000	2 000	8 500	9 000
LENGHWISE CUTTING LINE	0,27-1,4	0,2-1,2	25-1250	400	-	500/600	1500	1500	5 000	15 000
LENGHWISE CUTTING LINE SALICO/EMBOSS	0,20 -4,0	0,2-2,5	28-1650	500	-	406/508/610	2000	2000	8 000	15 000
CROSSWISE CUTTING LINE SALICO	0,3-4,0	0,3-1,5	300-1500	500	300-6000	-	-	-	3 000	3 000
CROSSWISE CUTTING LINE FIMI	-	0,4-3,0	300-1650	750	300-6000	-	-	-	-	3 000
LENGHWISE CUTTING LINE FIMI	-	0,4-5,0	21-1720	200 až 1200	-	508	-	2100	-	20 000

The Company is registered in the Companies Register kept by the Municipal Court in Prague, section B, enclosure 11701. Representative: Ing. Marián Manda, CSc. - Managing Director.

